

SAFETY DATA SHEET STP® Carb Spray Cleaner Professional

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended).

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name STP® Carb Spray Cleaner Professional

Product number 71500

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cleaning agent.

Uses advised againstNo specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier Energizer Trading Ltd

Sword House Totteridge Road High Wycombe HP13 6DG

UK

Tel: +44 845 602 1995 euregulatory@energizer.com

1.4. Emergency telephone number

Emergency telephone +44 1495 350234

Monday - Thursday: 0830 - 1700

Friday: 0830 - 1530

National emergency telephone Product information has been submitted to the UK National Poisons Information Service

number (NPIS) and is accessible to medical health professionals.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Aerosol 1 - H222, H229

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335, H336 STOT RE 2 - H373 Asp. Tox.

1 - H304

Environmental hazards Not Classified

Physicochemical Containers can burst violently or explode when heated, due to excessive pressure build-up.

When sprayed on a naked flame or any incandescent material the aerosol vapours can be

ignited.

2.2. Label elements

STP® Carb Spray Cleaner Professional

Hazard pictograms







Signal word

Danger

Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe vapour/ spray.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P314 Get medical advice/ attention if you feel unwell. P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/ container in accordance with national regulations.

Contains

acetone, xylene, 4-hydroxy-4-methylpentan-2-one, ethylbenzene

Detergent labelling

≥ 30% aliphatic hydrocarbons, 15 - < 30% aromatic hydrocarbons

Supplementary precautionary

statements

P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.

P332+P313 If skin irritation occurs: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTRE/doctor if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice/ attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hydrocarbons, C3-4-rich, petroleum distillate

25 - <50%

CAS number: 68512-91-4 EC number: 270-990-9

Classification

Flam. Gas 1A - H220 Press. Gas (Liq.) - H280

STP® Carb Spray Cleaner Professional

acetone		25 - <50%
CAS number: 67-64-1	EC number: 200-662-2	REACH registration number: 01- 2119471330-49-XXXX
Classification Flam. Liq. 2 - H225		
Eye Irrit. 2 - H319 STOT SE 3 - H336		

 xylene

 CAS number: 1330-20-7
 EC number: 215-535-7
 REACH registration number: 01-2119488216-32-XXXX

 Classification

 Flam. Liq. 3 - H226
 Acute Tox. 4 - H312

 Acute Tox. 4 - H332
 Skin Irrit. 2 - H315

 Eye Irrit. 2 - H319
 STOT SE 3 - H335

 STOT RE 2 - H373
 Asp. Tox. 1 - H304

4-hydroxy-4-methylpentan-2-one

10 - <25%

CAS number: 123-42-2 EC number: 204-626-7 REACH registration number: 01-

2119473975-21-XXXX

Classification

Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H335

ethylbenzene 2.5 - <5%

CAS number: 100-41-4 EC number: 202-849-4

Classification

Flam. Liq. 2 - H225 Acute Tox. 4 - H332 STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Chronic 3 - H412

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation Move

Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.

STP® Carb Spray Cleaner Professional

Ingestion Rinse mouth thoroughly with water. Move affected person to fresh air and keep warm and at

rest in a position comfortable for breathing. Keep affected person under observation. Do not induce vomiting unless under the direction of medical personnel. Get medical attention if any

discomfort continues.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Do not use

organic solvents. Get medical attention if any discomfort continues.

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15

minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion May cause discomfort if swallowed.

Skin contact Prolonged skin contact may cause redness and irritation.

Eye contact Prolonged contact may cause redness and/or tearing.

4.3. Indication of any immediate medical attention and special treatment needed

length of exposure.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Extinguish with the following media: Dry chemicals, sand, dolomite etc. Carbon dioxide (CO2).

Water spray, fog or mist.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

Bursting aerosol containers may be propelled from a fire at high speed.

Hazardous combustion

products

Thermal decomposition or combustion products may include the following substances: Oxides

of carbon. Toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during

firefighting

Use water to keep fire exposed containers cool and disperse vapours.

Special protective equipment

for firefighters

Use protective equipment appropriate for surrounding materials. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and

gloves) will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. Eliminate all

ignition sources if safe to do so. Avoid contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Wear protective clothing as described in Section 8 of this safety data sheet. No smoking, sparks, flames or other sources of ignition near spillage. Eliminate all ignition sources if safe to do so. Do not touch or walk into spilled material. Absorb in vermiculite, dry sand or earth and place into containers. Use only non-sparking tools. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

6.4. Reference to other sections

Reference to other sections See Section 11 for additional information on health hazards. For waste disposal, see Section

13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Wear protective clothing as described in

Section 8 of this safety data sheet. Keep away from heat, sparks and open flame. Provide

adequate ventilation.

Advice on general occupational hygiene

Avoid contact with eyes and prolonged skin contact. Good personal hygiene procedures should be implemented. Do not eat, drink or smoke when using this product. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in a cool and well-ventilated place. Keep away from heat, sparks and open flame. Take

precautionary measures against static discharges.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Hydrocarbons, C3-4-rich, petroleum distillate

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m³ Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m³

acetone

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³ Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

xylene

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³ Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³ Sk, BMGV

4-hydroxy-4-methylpentan-2-one

Long-term exposure limit (8-hour TWA): WEL 50 ppm 241 mg/m³ Short-term exposure limit (15-minute): WEL 75 ppm 362 mg/m³

ethylbenzene

Long-term exposure limit (8-hour TWA): WEL 100 ppm 441 mg/m³ Short-term exposure limit (15-minute): WEL 125 ppm 552 mg/m³ Sk

WEL = Workplace Exposure Limit. Sk = Can be absorbed through the skin. BMGV = Biological monitoring guidance value.

8.2. Exposure controls

STP® Carb Spray Cleaner Professional

Appropriate engineering

controls

Provide adequate ventilation. All handling should only take place in well-ventilated areas. Avoid inhalation of vapours and spray/mists. Use explosion-proof electrical, ventilating and

lighting equipment.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates

eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Wear tight-fitting, chemical splash goggles

or face shield.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if

a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Frequent changes are recommended.

Other skin and body

protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measuresDo not smoke in work area. Wash promptly with soap and water if skin becomes

contaminated. Wash at the end of each work shift and before eating, smoking and using the

toilet.

Respiratory protection Respiratory protection complying with an approved standard should be worn if a risk

assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective

equipment is suitable for its intended use and is 'CE'-marked.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Aerosol.

Colour Colourless.

Odour Hydrocarbons.

Odour threshold Not determined.

pH Not determined.

Melting point Not determined.

Initial boiling point and range Not determined.

Flash point Not determined.

Evaporation rate Not determined.

Evaporation factor Not determined.

Flammability (solid, gas) Not determined.

Upper/lower flammability or

explosive limits

Not determined.

Vapour pressure Not determined.

Vapour density Not determined.

Relative density Not determined.

Bulk density Not determined.

Partition coefficient Not determined.

Auto-ignition temperature Not determined.

STP® Carb Spray Cleaner Professional

Decomposition Temperature Not determined.

Viscosity Not determined.

Explosive properties Not considered to be explosive.

Oxidising properties The mixture itself has not been tested but none of the ingredient substances meet the criteria

for classification as oxidising.

9.2. Other information

Other information No information required.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Will not polymerise.

10.4. Conditions to avoid

Conditions to avoid Avoid exposing aerosol containers to high temperatures or direct sunlight. Avoid heat, flames

and other sources of ignition. Avoid the accumulation of vapours in low or confined areas.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a

hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Does not decompose when used and stored as recommended. Decomposition at ambient temperatures may generate the following substances: Carbon dioxide (CO2). Carbon

monoxide (CO). Acrid smoke or fumes.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅o) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

ATE dermal (mg/kg) 4,313.73

Acute toxicity - inhalation

Notes (inhalation LC₅₀)

Based on available data the classification criteria are not met.

ATE inhalation (gases ppm) 180,000.0

ATE inhalation (vapours mg/l) 39.29

Skin corrosion/irritation

Animal data Skin Irrit. 2 - H315

Serious eye damage/irritation

STP® Carb Spray Cleaner Professional

Based on available data the classification criteria are not met.

Serious eye damage/irritation Eye Irrit. 2 - H319

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vivo

Genotoxicity - in vitroBased on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure STOT SE 3 - H336

Specific target organ toxicity - repeated exposure

STOT - repeated exposure STOT RE 2 - H373 May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Aspiration hazard Asp. Tox. 1 - H304

Toxicological information on ingredients.

Hydrocarbons, C3-4-rich, petroleum distillate

Germ cell mutagenicity

Genotoxicity - in vivo Chromosome aberration: Negative. REACH dossier information.

Reproductive toxicity

Reproductive toxicity - One-generation study - NOAEC 10000 ppm, Inhalation, Rat P REACH dossier

fertility information.

Reproductive toxicity - Developmental toxicity: - NOAEC: 10426 ppm, Inhalation, Rat REACH dossier

development information.

acetone

Acute toxicity - oral

Acute toxicity oral (LD₅₀ 5,800.0

mg/kg)

Species Rat

Notes (oral LD₅₀) REACH dossier information.

ATE oral (mg/kg) 5,800.0

Serious eye damage/irritation

Serious eye Eye Irrit. 2 - H319 Causes serious eye irritation.

damage/irritation

Skin sensitisation

STP® Carb Spray Cleaner Professional

Skin sensitisation Guinea pig maximization test (GPMT) - Guinea pig: Not sensitising. REACH dossier

information.

Germ cell mutagenicity

Genotoxicity - in vitroGene mutation: Negative. REACH dossier information.

Carcinogenicity

Carcinogenicity NOEL 79 mg/, Mouse, Dermal, REACH dossier information.

Reproductive toxicity

Reproductive toxicity -

development

Maternal toxicity: - NOAEC: 2200 ppm, Inhalation, Rat REACH dossier information.

Specific target organ toxicity - single exposure

STOT - single exposure STOT SE 3 - H336 May cause drowsiness or dizziness.

xylene

Acute toxicity - oral

Acute toxicity oral (LD₅o

mg/kg)

5,251.0

Species Mouse

Notes (oral LD₅₀) REACH dossier information.

ATE oral (mg/kg) 5,251.0

Acute toxicity - dermal

Notes (dermal LD₅₀) cATpE: Converted Acute Toxicity Point Estimate.

ATE dermal (mg/kg) 1,100.0

Acute toxicity - inhalation

Notes (inhalation LC₅₀) cATpE: Converted Acute Toxicity Point Estimate.

ATE inhalation (vapours

mg/l)

11.0

Skin corrosion/irritation

Animal data Skin Irrit. 2 - H315 Causes skin irritation.

Serious eye damage/irritation

Serious eye damage/irritation

Dose: 0.1 ml, 72 hours, Rabbit REACH dossier information. Moderately irritating.

Germ cell mutagenicity

Genotoxicity - in vitro Chromosome aberration: Negative. REACH dossier information.

Genotoxicity - in vivo Chromosome aberration: Negative. REACH dossier information.

Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

Reproductive toxicity

Reproductive toxicity -

fertility

Two-generation study - NOAEC ≥500 ppm, Inhalation, Rat P, F1 REACH dossier

information.

STP® Carb Spray Cleaner Professional

Reproductive toxicity -

Developmental toxicity: - NOAEC: ≥500 ppm, Inhalation, Rat REACH dossier

development

Specific target organ toxicity - single exposure

information.

STOT - single exposure STOT SE 3 - H335 May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure STOT RE 2 - H373 May cause damage to organs through prolonged or repeated

exposure.

Target organs Central nervous system Kidneys Liver

Aspiration hazard

Aspiration hazard Asp. Tox. 1 - H304 May be fatal if swallowed and enters airways.

4-hydroxy-4-methylpentan-2-one

Acute toxicity - oral

Acute toxicity oral (LD₅o

mg/kg)

3,002.0

Species Rat

Notes (oral LD₅₀) REACH dossier information.

ATE oral (mg/kg) 3,002.0

Skin corrosion/irritation

Animal data Dose: 0.5 ml, 24 hours, Rabbit Erythema/eschar score: No erythema (0). Oedema

score: No oedema (0). REACH dossier information.

Serious eye damage/irritation

Serious eye

Dose: 0.1 ml, 1 hour, Rabbit REACH dossier information. Irritating.

damage/irritation

Skin sensitisation

Skin sensitisation Guinea pig maximization test (GPMT) - Guinea pig: Not sensitising. REACH dossier

information.

Germ cell mutagenicity

Genotoxicity - in vitroGene mutation: Negative. REACH dossier information.

Carcinogenicity

Carcinogenicity NOAEC 1847 mg/m³, Inhalation, Rat REACH dossier information. Read across

data.

Reproductive toxicity

Reproductive toxicity -

Fertility - NOAEL 300 mg/kg/day, Oral, Rat P REACH dossier information.

fertility

Specific target organ toxicity - single exposure

STOT - single exposure STOT SE 3 - H335 May cause respiratory irritation.

Target organs Respiratory tract

ethylbenzene

Acute toxicity - oral

STP® Carb Spray Cleaner Professional

Acute toxicity oral (LD50

mg/kg)

3,500.0

Species Rat

ATE oral (mg/kg) 3,500.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 15,400.0

mg/kg)

Species Rabbit

15,400.0 ATE dermal (mg/kg)

Acute toxicity - inhalation

Notes (inhalation LC50) Converted acute toxicity point estimate (cATpE) Acute Tox. 4 - H332 Harmful if

inhaled.

ATE inhalation (gases

ppm)

4,500.0

ATE inhalation (vapours

mg/l)

11.0

Skin corrosion/irritation

Animal data Dose: 0.01 ml, 24 hours, Rabbit Moderately irritating.

Germ cell mutagenicity

Genotoxicity - in vitro Chromosome aberration: Negative.

Genotoxicity - in vivo Chromosome aberration: Negative.

Carcinogenicity

NOAEC 250 ppm, Oral, Rat Carcinogenicity

IARC carcinogenicity IARC Group 2B Possibly carcinogenic to humans.

Reproductive toxicity

Reproductive toxicity -

fertility

Two-generation study - NOAEC 500 ppm, Inhalation, Rat P

Reproductive toxicity -

development

Maternal toxicity: - NOAEC: 500 ppm, Inhalation, Rat

SECTION 12: Ecological information

12.1. Toxicity

Toxicity The product is not expected to be toxic to aquatic organisms. However, large or frequent spills

may have hazardous effects on the environment.

Ecological information on ingredients.

Hydrocarbons, C3-4-rich, petroleum distillate

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 49.47 mg/l, Fish

REACH dossier information.

QSAR

STP® Carb Spray Cleaner Professional

acetone

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 8120 mg/l, Pimephales promelas (Fat-head Minnow)

REACH dossier information.

Acute toxicity - aquatic

LC₅₀, 48 hours: 8800 mg/l, Daphnia pulex

invertebrates

REACH dossier information.

Acute toxicity - aquatic

plants

NOEC, 8 days: 530 mg/l, Microcystis aeruginosa

REACH dossier information.

EC₁₂, 30 minutes: 1000 mg/l, Activated sludge Acute toxicity -

microorganisms REACH dossier information.

Acute toxicity - terrestrial LC₅₀, 48 hours: 100 - 1000 µg/cm², Eisenia Fetida (Earthworm)

REACH dossier information.

Chronic aquatic toxicity

Chronic toxicity - aquatic

invertebrates

NOEC, 28 days: 2212 mg/l, Daphnia magna LOEC, 28 days: 2212 mg/l, Daphnia magna

REACH dossier information.

xylene

Acute aquatic toxicity

LC₅₀, 96 hours: 2.6 mg/l, Oncorhynchus mykiss (Rainbow trout) Acute toxicity - fish

REACH dossier information.

Read-across data.

Acute toxicity - aquatic

invertebrates

IC₅₀, 24 hours: 1 mg/l, Daphnia magna

REACH dossier information.

Read-across data.

Acute toxicity - aquatic

plants

NOEC, 73 hours: 0.44 mg/l, Pseudokirchneriella subcapitata EC₅₀, 73 hours: 2.2 mg/l, Pseudokirchneriella subcapitata

REACH dossier information.

Read-across data.

Acute toxicity -EC₅₀, 24 hours: 96 mg/l, Nitrosomonas

microorganisms REACH dossier information.

Read-across data.

Chronic aquatic toxicity

Chronic toxicity - fish early NOEC, 56 days: > 1.3 mg/l, Oncorhynchus mykiss (Rainbow trout)

life stage

REACH dossier information.

Chronic toxicity - aquatic

invertebrates

NOEC, 7 days: 1.17 mg/l, Ceriodaphnia dubia

REACH dossier information.

Read-across data.

4-hydroxy-4-methylpentan-2-one

Acute aquatic toxicity

LC₅₀, 96 hours: > 100 mg/l, Oryzias latipes (Red killifish) Acute toxicity - fish

REACH dossier information.

STP® Carb Spray Cleaner Professional

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: > 1000 mg/l, Daphnia magna NOEC, 48 hours: 1000 mg/l, Daphnia magna

REACH dossier information.

Acute toxicity - aquatic

plants

EC₅₀, 72 hours: > 1000 mg/l, Pseudokirchneriella subcapitata NOEC, 72 hours: 1000 mg/l, Pseudokirchneriella subcapitata

REACH dossier information.

Acute toxicity -EC₅₀, 3 hours: > 1000 mg/l, Activated sludge

microorganisms REACH dossier information.

Chronic aquatic toxicity

Chronic toxicity - aquatic

invertebrates

LC₅₀, 14 days: > 100 mg/l, Daphnia magna LC₅₀, 21 days: > 100 mg/l, Daphnia magna EC₅₀, 14 days: > 100 mg/l, Daphnia magna EC₅₀, 21 days: > 100 mg/l, Daphnia magna NOEC, 21 days: 100 mg/l, Daphnia magna

REACH dossier information.

ethylbenzene

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 4.2 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: 1.8 - 2.4 mg/l, Daphnia magna EC₅₀, 24 hours: 2.4 - 2.8 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC₅₀, 24 hours: 8 mg/l, Skeletonema costatum EC₅₀, 48 hours: 7.5 mg/l, Skeletonema costatum EC₅₀, 72 hours: 4.9 mg/l, Skeletonema costatum EC₅₀, 96 hours: 7.7 mg/l, Skeletonema costatum

NOEC, 96 hours: 4.5 mg/l, Skeletonema costatum

Acute toxicity microorganisms EC₅₀, 24 hours: 96 mg/l, Nitrosomonas

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

Ecological information on ingredients.

Hydrocarbons, C3-4-rich, petroleum distillate

Phototransformation Water - DT₅₀: 1906 days

REACH dossier information.

Calculation method.

Biodegradation Water - Degradation (100%): 385.5 hours

REACH dossier information.

The substance is readily biodegradable.

acetone

Water - DT₅₀ : ~ 10 days **Phototransformation**

REACH dossier information.

STP® Carb Spray Cleaner Professional

Biodegradation Water - Degradation (25.5 - 36.7%): 281 days

Water - Degradation (90.9%): 28 days

REACH dossier information.

The substance is readily biodegradable.

xylene

Phototransformation Water - DT₅₀ : 1.09 days

REACH dossier information.

Read-across data.

Biodegradation Water - ThOD (68%): 10 days

Water - ThOD (87.8%): 28 days REACH dossier information.

Read-across data.

The substance is readily biodegradable.

4-hydroxy-4-methylpentan-2-one

Biodegradation Water - Degradation (98.51%): 28 days

REACH dossier information.

The substance is readily biodegradable.

ethylbenzene

Phototransformation Water - Degradation (50%): 2.3 days

Biodegradation Water - Degradation (70 - 80%): 28 days

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

Ecological information on ingredients.

Hydrocarbons, C3-4-rich, petroleum distillate

Partition coefficient log Pow: 2.3058 REACH dossier information. QSAR

acetone

Partition coefficient log Pow: -0.24 REACH dossier information.

xylene

Bioaccumulative potential BCF: 5.5 - 12.2, Oncorhynchus mykiss (Rainbow trout) REACH dossier information.

Partition coefficient log Pow: 3.12 REACH dossier information. Read-across data.

ethylbenzene

Bioaccumulative potential BCF: 1, Oncorhynchus kisutch (Coho salmon)

Partition coefficient log Pow: 3.6

12.4. Mobility in soil

Mobility The product is insoluble in water.

Ecological information on ingredients.

acetone

Henry's law constant 2.929 Pa m³/mol @ 25°C REACH dossier information.

Surface tension 26.2 mN/m @ 0°C 23.7 mN/m @ 20°C 21.2 mN/m @ 40°C 18.7 mN/m @ 60°C

16.2 mN/m @ 80°C REACH dossier information.

xylene

Adsorption/desorption

coefficient

Water - log Koc: 2.73 Read-across data. REACH dossier information.

Henry's law constant 623 - 665 Pa m³/mol @ 25°C QSAR REACH dossier information.

Surface tension 28.75 mN/m @ 25°C REACH dossier information. Read-across data.

ethylbenzene

Henry's law constant 0.008 atm m³/mol @ 25°C

Surface tension 71.2 mN/m @ 23°C

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of waste product or used containers in accordance with local regulations Do not

puncture or incinerate, even when empty.

Disposal methods Waste should not be disposed of untreated to the sewer unless fully compliant with the

requirements of the local water authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

UN No. (ADN) 1950

14.2. UN proper shipping name

Proper shipping name

AEROSOLS

(ADR/RID)

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID classification code 5F

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

ADN class 2.1

Transport labels



14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-D, S-U

ADR transport category 2

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations EH40/2005 Workplace exposure limits.

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended). The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use)

(Amendment etc.) (EU Exit) Regulations 2019, SI 2019/720 (as amended).

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Commission Regulation (EU) No 2015/830 of 28 May 2015.

Council Directive of 20 May 1975 on the approximation of the laws of the Member States

relating to aerosol dispensers (75/324/EEC) (as amended).

Regulation (EC) No 648/2004 of the European Parliament and of the Council of 31 March

2004 on detergents (as amended).

STP® Carb Spray Cleaner Professional

Explosives precursors Regulated explosives precursor. Regulation (EU) No 2019/1148 of the European Parliament

and of the Council of 20 June 2019 on the marketing and use of explosives precursors:

Contains a substance or substances listed in Annex II: acetone 25 - <50%

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet ADR: European Agreement concerning the International Carriage of Dangerous Goods by

RID: European Agreement concerning the International Carriage of Dangerous Goods by

Rail.

IMDG: International Maritime Dangerous Goods.

IATA: International Air Transport Association.

ADN: European Agreement concerning the International Carriage of Dangerous Goods by

Inland Waterways.

ATE: Acute Toxicity Estimate. DNEL: Derived No Effect Level.

LC₅₀: Lethal Concentration to 50 % of a test population.

LD₅₀: Lethal Dose to 50% of a test population (Median Lethal Dose).

PBT: Persistent, Bioaccumulative and Toxic substance. vPvB: Very Persistent and Very Bioaccumulative.

BCF: Bioconcentration Factor.

Classification procedures according to Regulation (EC) 1272/2008

Aerosol 1 - H222, H229: Expert judgement. Skin Irrit. 2 - H315, Eye Irrit. 2 - H319, STOT SE 3

- H336, Asp. Tox. 1 - H304, STOT RE 2 - H373: Calculation method.

Revision comments Section 1: Identification of the substance/mixture and of the company/undertaking // 1.3.

Details of the supplier of the safety data sheet.

Revision date 02/06/2021

Revision 13

Supersedes date 21/01/2021

SDS number 414

Hazard statements in full

H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H229 Pressurised container: may burst if heated.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs (Hearing organs) through prolonged or repeated exposure.

H373 May cause damage to organs through prolonged or repeated exposure.

H373 May cause damage to organs (Central nervous system, Kidneys, Liver) through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

The information supplied here is accurate to the best knowledge and belief of Energizer Trading Ltd, it is however, not intended as a warranty or representation, and should not be construed as such, for which Energizer Trading Ltd assumes any legal responsibility. Any information or advice obtained from Energizer Trading Ltd other than by means of this publication, and whether relating to Energizer Trading Ltd's products or other materials is also given in good faith. It remains at all times the responsibility of the customer, and user, to ensure that the materials are suitable for the particular purpose intended. Materials not manufactured, or supplied, by Energizer Trading Ltd when used instead of, or in conjunction with materials supplied by Energizer Trading Ltd, it is the customer's responsibility to ensure that all technical, and other information related to such materials is obtained from the manufacturer or supplier. Energizer Trading Ltd accepts no liability for the data contained within this document, as the information herein may be applied under conditions beyond our control, and in situations with which we may be unfamiliar. The information contained within this document is furnished upon condition that the customer and user of this product makes his own determination of the suitability of the product for his particular purpose.